



Тел.: +996 555771513,
email: info@ravenol.kg

RAVENOL Calibration Fluid

RAVENOL Calibration Fluid is a test fluid for the calibration of diesel injection pumps and as a corrosion preventive oil for the internal preservation of fuel systems.

Application Notes

RAVENOL Calibration Fluid V is used as a test fluid for the calibration of diesel injection pumps and as a corrosion preventive oil for the internal preservation of fuel systems.

Quality Classifications

RAVENOL Calibration Fluid is tried and tested for aggregates specifying:

Specifications

ISO 4113, SAE J 967D, MB 133.0

Characteristic

RAVENOL Calibration Fluid offers:

- Excellent wear protection
- Excellent corrosion protect
- Low tendency to foam

RAVENOL Calibration Fluid is a test fluid for the calibration of diesel injection pumps and as a corrosion preventive oil for the internal preservation of fuel systems.

Application Notes

RAVENOL Calibration Fluid V is used as a test fluid for the calibration of diesel injection pumps and as a corrosion preventive oil for the internal

preservation of fuel systems.

Quality Classifications

RAVENOL Calibration Fluid is tried and tested for aggregates specifying:

Specifications

ISO 4113, SAE J 967D, MB 133.0

Characteristic

RAVENOL Calibration Fluid offers:

- Excellent wear protection
- Excellent corrosion protect
- Low tendency to foam

Characteristics	Unit	Data	Audit
Colour		farblos	visual
Density at 20°C	kg/m ³	826	EN ISO 12185
Viscosity at 40°C	mm ² /s	2,62	DIN 51 562
Flash point (COC)	°C	90	DIN ISO 2592
Pourpoint	°C	-40	DIN ISO 3016
TBN base number	mg KOH/g	2,5	DIN ISO 3771

All indicated data are approximate values and are subject to the commercial fluctuations.