



Тел.: +996 555771513,
email: info@ravenol.kg

RAVENOL Getriebeöl CLP 68

RAVENOL Getriebeoel CLP 68 is a high quality, mineral-based gear oil formulated with lead-free high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity. **RAVENOL Getriebeoel CLP 68** has a low pour point and therefore a very good cold behaviour.

Application Notes

RAVENOL Getriebeoel CLP 68 can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

Quality Classifications

RAVENOL Getriebeoel CLP 68 is tried and tested for aggregates specifying:

Specifications

DIN 51 517 Part 3, FZG 12, US Steel 224

Characteristic

RAVENOL Getriebeöl CLP 68 offers:

- A very good, stable high-pressure impact capacity.
- Resistant characteristics at high temperatures.
- A good rust and corrosion impeding effect.
- Excellent wear protection.
- Very good anti-foaming characteristics.
- A low pour point.
- Very good cold behaviour.

RAVENOL Getriebeoel CLP 68 is a high quality, mineral-based gear oil

formulated with lead-free high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity. **RAVENOL Getriebeöl CLP 68** has a low pour point and therefore a very good cold behaviour.

Application Notes

RAVENOL Getriebeöl CLP 68 can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

Quality Classifications

RAVENOL Getriebeöl CLP 68 is tried and tested for aggregates specifying:

Specifications

DIN 51 517 Part 3, FZG 12, US Steel 224

Characteristic

RAVENOL Getriebeöl CLP 68 offers:

- A very good, stable high-pressure impact capacity.
- Resistant characteristics at high temperatures.
- A good rust and corrosion impeding effect.
- Excellent wear protection.
- Very good anti-foaming characteristics.
- A low pour point.
- Very good cold behaviour.

| Characteristics | Unit | Data | Audit |
|--------------------|--------------------|-------|--------------|
| Colour | | braun | visual |
| Density at 20°C | kg/m ³ | 879 | EN ISO 12185 |
| Viscosity at 40°C | mm ² /s | 67,0 | DIN 51 562 |
| Viscosity at 100°C | mm ² /s | 8,6 | DIN 51 562 |
| Viscosity index VI | | 100 | DIN ISO 2909 |
| Flash point (COC) | °C | 220 | DIN ISO 2592 |

| Characteristics | Unit | Data | Audit |
|------------------------|-------------|-------------|--------------|
| Pourpoint | °C | -24 | DIN ISO 3016 |

All indicated data are approximate values and are subject to the commercial fluctuations.