



Тел.: +996 555771513,

email: info@ravenol.kg

## **RAVENOL Getriebeöl CLP 320**

**RAVENOL Getriebeöl CLP 320** is high-grade industrial gear oil, based on mineral oil, formulated with lead-free EP-additives. Due to its special combination a very good, stable high-pressure absorption is achieved for shock load.

**RAVENOL Getriebeöl CLP 320** has a low pour point and therefore very good low temperature properties.

### **Application Notes**

**RAVENOL Getriebeöl CLP 320** is to be used for the lubrication of almost any type of industrial gear box, even when exposed to heavy duty and shock loads.

### **Quality Classifications**

#### **Specifications**

FZG 12, Vickers Vane Pump, DIN 51 517 Part 3, US Steel 224, Eickhoff  
Bergbautechnik: Bestätigung für die Verwendung in den Getrieberäumen

### **Characteristic**

**RAVENOL Getriebeöl CLP 320** offers:

- a very good resistance towards high pressures and shock loads
- a good resistance against high temperatures
- good corrosion preventing properties
- an excellent prevention from wear
- a very good activity against foaming
- a low pour point

**RAVENOL Getriebeöl CLP 320** is high-grade industrial gear oil, based on

mineral oil, formulated with lead-free EP-additives. Due to its special combination a very good, stable high-pressure absorption is achieved for shock load.

**RAVENOL Getriebeöl CLP 320** has a low pour point and therefore very good low temperature properties.

## Application Notes

**RAVENOL Getriebeöl CLP 320** is to be used for the lubrication of almost any type of industrial gear box, even when exposed to heavy duty and shock loads.

## Quality Classifications

### Specifications

FZG 12, Vickers Vane Pump, DIN 51 517 Part 3, US Steel 224, Eickhoff Bergbautechnik: Bestätigung für die Verwendung in den Getrieberäumen

### Characteristic

**RAVENOL Getriebeöl CLP 320** offers:

- a very good resistance towards high pressures and shock loads
- a good resistance against high temperatures
- good corrosion preventing properties
- an excellent prevention from wear
- a very good activity against foaming
- a low pour point

Characteristics	Unit	Data	Audit
Colour		yellow brown	visual
Density at 20°C	kg/m <sup>3</sup>	895	EN ISO 12185
Viscosity at 40°C	mm <sup>2</sup> /s	327,6	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	24,3	DIN 51 562
Viscosity index VI		95	DIN ISO 2909
Flash point (COC)	°C	244	DIN ISO 2592

<b>Characteristics</b>	<b>Unit</b>	<b>Data</b>	<b>Audit</b>
Pourpoint	°C	-9	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.