



Тел.: +996 555771513,
email: info@ravenol.kg

RAVENOL Getriebeöl CLP 460

RAVENOL Getriebeoel CLP 460 is a high quality, mineral-based gear oil formulated with lead-free high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity.

RAVENOL Getriebeoel CLP 460 has a low pour point and therefore a good cold behaviour.

Application Notes

RAVENOL Getriebeoel CLP 460 can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

Quality Classifications

RAVENOL Getriebeoel CLP 460 is tried and tested for aggregates specifying:

Specifications

DIN 51 517 Part 3, FZG 12, US Steel 224

Practice and tested in aggregates with filling

AGMA 9005-D94, Cincinnati Milacron, Clean Panel Coker, S-200 Oxidation Tubes

Characteristic

RAVENOL Getriebeoel CLP 460 offers:

- A very good, stable high-pressure impact capacity.
- Resistant characteristics at high temperatures.
- A good rust and corrosion impeding effect.
- Excellent wear protection.
- Very good anti-foaming characteristics.

- A low pour point.
- Good cold behaviour

RAVENOL Getriebeoel CLP 460 is a high quality, mineral-based gear oil formulated with lead-free high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity.

RAVENOL Getriebeoel CLP 460 has a low pour point and therefore a good cold behaviour.

Application Notes

RAVENOL Getriebeoel CLP 460 can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

Quality Classifications

RAVENOL Getriebeoel CLP 460 is tried and tested for aggregates specifying:

Specifications

DIN 51 517 Part 3, FZG 12, US Steel 224

Practice and tested in aggregates with filling

AGMA 9005-D94, Cincinnati Milacron, Clean Panel Coker, S-200 Oxidation Tubes

Characteristic

RAVENOL Getriebeoel CLP 460 offers:

- A very good, stable high-pressure impact capacity.
- Resistant characteristics at high temperatures.
- A good rust and corrosion impeding effect.
- Excellent wear protection.
- Very good anti-foaming characteristics.
- A low pour point.
- Good cold behaviour

Characteristics	Unit	Data	Audit
Colour		yellow brown	visual

Characteristics	Unit	Data	Audit
Density at 20°C	kg/m ³	900	EN ISO 12185
Viscosity at 40°C	mm ² /s	490,3	DIN 51 562
Viscosity at 100°C	mm ² /s	31,2	DIN 51 562
Viscosity index VI		93	DIN ISO 2909
Flash point (COC)	°C	224	DIN ISO 2592
Pourpoint	°C	-12	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.