



Тел.: +996 555771513,
email: info@ravenol.kg

RAVENOL Getriebeöl PAO CLP 460

RAVENOL Getriebeöl CLP 460 is premium performance, extreme pressure lubricant designed for enclosed industrial gears and bearings operating under severe load conditions and in wide extremes of temperature.

RAVENOL Getriebeöl CLP 460 is formulated using PAO synthetic base oils and additive technologies to deliver excellent wear properties, outstanding extreme temperature performance for extended component and fluid life.

RAVENOL Getriebeöl PAO CLP 460 enhances gear box efficiency over a wide temperature range and an reduce power consumption.

Application Notes

RAVENOL Getriebeöl CLP 460 is recommended for enclosed industrial gear drives and bearings particularly where they are operated under heavy duty conditions such as heavy loading, slow speed, shock loads and in wide extremes of temperature.

The tough oil film of **RAVENOL Getriebeöl CLP 460** and low coefficient of friction save energy in gearboxes. The high viscosity index of **RAVENOL Getriebeöl CLP 460** means they retain their viscosity at high operating temperatures. This often allows the use of a lower ISO grade than with conventional gear oil resulting in even greater energy savings.

RAVENOL Getriebeöl CLP 460 is designed to combat these conditions and will run cooler while maintaining a high lubricant film strength. For gearboxes that operate outdoors, **RAVENOL Getriebeöl CLP 460** is capable of operating at temperatures as low as -30°C or below.

When converting a gearbox to **RAVENOL Getriebeöl CLP 460**, it is recommended to be cleaned and flushed first to gain the full benefit of the product.

RAVENOL Getriebeöl CLP 460 is compatible with mineral oils,

polyalphaolefin lubricants and most seal materials except natural rubber.

RAVENOL Getriebeöl CLP 460 operates over the temperature range from -30°C to 120°C.

Quality Classifications

Specifications

DIN 51 517 Part 3, US Steel 224, AGMA 9005-D94, Cincinnati Milacron, Clean Panel Coker, S-200 Oxidation Tubes

Characteristic

RAVENOL Getriebeöl CLP 460 offers:

- Extends equipment life
- Designed to protect equipment being operated under tough high load conditions
- Improves operating reliability over a wide range of gearbox loads
- Better film strength and extreme pressure properties than the leading global competitor synthetic for extended gear and bearing life
- Reduces likelihood of seizure, scuffing or spalling of gear teeth and bearings under high load conditions
- Synthetic formulation reduces friction, Energy efficient over a wide temperature range
- Excellent extreme temperature performance protects your equipment in the most extreme temperature conditions
- Wider range of service temperatures with high Viscosity Index (VI) for a wide temperature range
- Protects against water damage provides excellent resistance to rust and copper corrosion

RAVENOL Getriebeöl CLP 460 is premium performance, extreme pressure lubricant designed for enclosed industrial gears and bearings operating under severe load conditions and in wide extremes of temperature.

RAVENOL Getriebeöl CLP 460 is formulated using PAO synthetic base oils

and additive technologies to deliver excellent wear properties, outstanding extreme temperature performance for extended component and fluid life.

RAVENOL Getriebeöl PAO CLP 460 enhances gear box efficiency over a wide temperature range and an reduce power consumption.

Application Notes

RAVENOL Getriebeöl CLP 460 is recommended for enclosed industrial gear drives and bearings particularly where they are operated under heavy duty conditions such as heavy loading, slow speed, shock loads and in wide extremes of temperature.

The tough oil film of **RAVENOL Getriebeöl CLP 460** and low coefficient of friction save energy in gearboxes. The high viscosity index of **RAVENOL Getriebeöl CLP 460** means they retain their viscosity at high operating temperatures. This often allows the use of a lower ISO grade than with conventional gear oil resulting in even greater energy savings.

RAVENOL Getriebeöl CLP 460 is designed to combat these conditions and will run cooler while maintaining a high lubricant film strength. For gearboxes that operate outdoors, **RAVENOL Getriebeöl CLP 460** is capable of operating at temperatures as low as -30°C or below.

When converting a gearbox to **RAVENOL Getriebeöl CLP 460**, it is recommended to be cleaned and flushed first to gain the full benefit of the product.

RAVENOL Getriebeöl CLP 460 is compatible with mineral oils, polyalphaolefin lubricants and most seal materials except natural rubber.

RAVENOL Getriebeöl CLP 460 operates over the temperature range from -30°C to 120°C.

Quality Classifications

Specifications

DIN 51 517 Part 3, US Steel 224, AGMA 9005-D94, Cincinnati Milacron, Clean Panel Coker, S-200 Oxidation Tubes

Characteristic

RAVENOL Getriebeöl CLP 460 offers:

- Extends equipment life
- Designed to protect equipment being operated under tough high load conditions
- Improves operating reliability over a wide range of gearbox loads
- Better film strength and extreme pressure properties than the leading global competitor synthetic for extended gear and bearing life
- Reduces likelihood of seizure, scuffing or spalling of gear teeth and bearings under high load conditions
- Synthetic formulation reduces friction, Energy efficient over a wide temperature range
- Excellent extreme temperature performance protects your equipment in the most extreme temperature conditions
- Wider range of service temperatures with high Viscosity Index (VI) for a wide temperature range
- Protects against water damage provides excellent resistance to rust and copper corrosion

Characteristics	Unit	Data	Audit
Colour		hellgelb	visual
Density at 20°C	kg/m ³	854	EN ISO 12185
Viscosity at 40°C	mm ² /s	453,6	DIN 51 562
Viscosity at 100°C	mm ² /s	58,7	DIN 51 562
Viscosity index VI		200	DIN ISO 2909
Flash point (COC)	°C	268	DIN ISO 2592
Pourpoint	°C	-45	DIN ISO 3016
Rust check, method A&B	24h	1a	ASTM D130

All indicated data are approximate values and are subject to the commercial fluctuations.