



Тел.: +996 555771513,
email: info@ravenol.kg

RAVENOL Umlauföl 460

RAVENOL Umlauföl 460 is a lubricant for roller bearings based on high-grade base oils and specially selected additives to achieve effective protection against rust and corrosion as well as excellent demulsifying properties.

Very good, stable viscosity-temperature characteristics are achieved thanks to the special combination of active ingredients of **RAVENOL Umlauföl 460**.

Application Notes

RAVENOL Umlauföl 460 can be used as a lubricant in almost all industrial transmissions, thanks to its very good properties, unless an EP (extreme pressure) engine oil is specified. It is especially suited for central circulation systems in rolling plants, in particular for hydrodynamic and hydrostatic bearings (Demag, Morgoil, Mesta and others) as well as similar application in other industrial sectors.

Specifications

DIN 51 517 Teil 2, SMS SIEMAG - MORGOIL® Schmierölspezifikation, SN 180-Teil 4: 2009-07, SN 180-Teil 3: 2009-06

Characteristic

RAVENOL Umlauföl 460 offers:

- high resistance against oxidation and sludge formation
- good anti-rust and anti-corrosive characteristics
- excellent wear protection
- very good protection against foaming
- good air release properties
- high aging resistance

RAVENOL Umlauföl 460 is a lubricant for roller bearings based on high-

grade base oils and specially selected additives to achieve effective protection against rust and corrosion as well as excellent demulsifying properties.

Very good, stable viscosity-temperature characteristics are achieved thanks to the special combination of active ingredients of **RAVENOL Umlaufoel 460**.

Application Notes

RAVENOL Umlaufoel 460 can be used as a lubricant in almost all industrial transmissions, thanks to its very good properties, unless an EP (extreme pressure) engine oil is specified. It is especially suited for central circulation systems in rolling plants, in particular for hydrodynamic and hydrostatic bearings (Demag, Morgoil, Mesta and others) as well as similar application in other industrial sectors.

Specifications

DIN 51 517 Teil 2, SMS SIEMAG - MORGOIL® Schmierölspezifikation, SN 180-Teil 4: 2009-07, SN 180-Teil 3: 2009-06

Characteristic

RAVENOL Umlauföl 460 offers:

- high resistance against oxidation and sludge formation
- good anti-rust and anti-corrosive characteristics
- excellent wear protection
- very good protection against foaming
- good air release properties
- high aging resistance

Characteristics	Unit	Data	Audit
Colour		gelbbraun	visual
Density at 20°C	kg/m ³	902	EN ISO 12185
Viscosity at 40°C	mm ² /s	463	DIN 51562
Viscosity at 100°C	mm ² /s	30	DIN 51 562
Viscosity index VI		94	DIN ISO 2909
Flash point (COC)	°C	304	DIN ISO 2592

Characteristics	Unit	Data	Audit
Pourpoint	°C	-15	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.