



Тел.: +996 555771513,  
email: info@ravenol.kg

## **RAVENOL Bettbahnöl 46**

**RAVENOL Bettbahnöl 46** is mineral slide way oil CGLP.

**RAVENOL Bettbahnöl 46** is characterized by good lubricating and sliding properties as well as high tackiness.

**RAVENOL Bettbahnöl 46** is formulated with mineral base oils and contains additives and corrosion inhibitors to prevent rust formation and stains on slide ways and track surfaces.

**RAVENOL Bettbahnöl 46** is compatible with most of drilling-, cutting or grinding emulsions. The lubricant film of the slide way oil is not washed off.

### **Application Notes**

**RAVENOL Bettbahnöl 46** can be used for all types of lubrication systems such as pressure, circulating or central lubrication. If necessary it can be applied manually. It can also be used for lubricating bearings and gear boxes.

### **Quality Classifications**

**RAVENOL Bettbahnöl 46** is tried and tested for aggregates specifying:

#### **Specifications**

DIN 51 502: CGLP

#### **Characteristic**

**RAVENOL Bettbahnöl 46** offers:

- Very good stick-slip characteristics
- High tackiness
- Good corrosion protection, no rust and stain formation
- Resistance to aqueous metalworking fluids
- Good demulsification

**RAVENOL Bettbahnöl 46** is mineral slide way oil CGLP.

**RAVENOL Bettbahnöl 46** is characterized by good lubricating and sliding properties as well as high tackiness.

**RAVENOL Bettbahnöl 46** is formulated with mineral base oils and contains additives and corrosion inhibitors to prevent rust formation and stains on slide ways and track surfaces.

**RAVENOL Bettbahnöl 46** is compatible with most of drilling-, cutting or grinding emulsions. The lubricant film of the slide way oil is not washed off.

## Application Notes

**RAVENOL Bettbahnöl 46** can be used for all types of lubrication systems such as pressure, circulating or central lubrication. If necessary it can be applied manually. It can also be used for lubricating bearings and gear boxes.

## Quality Classifications

**RAVENOL Bettbahnöl 46** is tried and tested for aggregates specifying:

### Specifications

DIN 51 502: CGLP

## Characteristic

**RAVENOL Bettbahnöl 46** offers:

- Very good stick-slip characteristics
- High tackiness
- Good corrosion protection, no rust and stain formation
- Resistance to aqueous metalworking fluids
- Good demulsification

Characteristics	Unit	Data	Audit
Colour		brown	visual
Density at 20°C	kg/m <sup>3</sup>	865	EN ISO 12185

<b>Characteristics</b>	<b>Unit</b>	<b>Data</b>	<b>Audit</b>
Viscosity at 40°C	mm <sup>2</sup> /s	46,0	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	7,1	DIN 51 562
Viscosity index VI		114	DIN ISO 2909
Flash point (COC)	°C	220	DIN ISO 2592
Pourpoint	°C	-15	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.